





GP750P

- · 630W 6100K LED.
- · Extremely even spot with flawless field consistency.
- · 6°-50° wide motorized zoom for precious control of projection area.
- CMY + CTO + color wheel(6+CRI filter+open) color mixing system that delivers deeply saturated colors.
- · 1 rotating gobo wheel(7+open) and 1 animation wheel.
- · Razor sharp shutter framing and elegant gobo shaping.
- · Indestructible weather-proof IP65 construction.
- · RDM, DMX and Art-Net control









Light Source:	638W LED
Output:	21000 lm
Illuminance:	74000 lux @ 5m / 6°
Color Temperature:	6100K
Beam Angle:	6°~50°
Lamp Life:	20K hrs
Color Mixing:	CMY+CTO+color wheel(7+open)
Gobo:	1 rotating gobo wheel(7+open)
Animation:	1 animation wheel
Shutter System:	4 independent blades±35°, rotatable±60°
Focus:	Motorized
Frost:	5° 0%~100% linear
Strobe:	0~30Hz

Zoom:	8x + motorized linear (6-50°)
Dimming:	4 dimming curves
Prism:	Bi-directional rotating 4-facet
Ambient:	-10°C ~ 45°C
Control:	DMX512/RDM/Art-Net/Wireless(optional)
DMX Channel:	22CH
Data Connections:	IP DMX IN/OUT
Power Connections:	IP Power IN/OUT
Cooling:	3DVC heat sink with noiseless fan
Display:	OLED display
Dimension:	514.5*324*249 mm
Weight	24 kg

CMY

Animation

Framming Shutter





