



1500W IP66 High Output LED Moving Profile

Beam, Spot, Wash, Profile 4-in-1

- 1500W 6000K LED engine
- Up to 60000 lumens output
- Ultra-wide zoom range: 3.8° ~ 54°
- Razor sharp shutter framing and elegant gobo shaping
- Extremely even spot with flawless field consistency
- Incoporating the latest advances of color wheel+CMY+CTO system
- Featuring animation wheel, frost, rotating gobo wheel and dual 4-f linear/circular prism
- Linear frost adjustable from light to heavy
- New ultra-linear 22-bit dimming guarantees smooth fades and flick-free output
- Rapid, smooth, quiet pan/tilt rotation
- Reset-free absolute positioning
- Rugged IP66 tour-graded construction for all-round protection for fixtures in any applications
- DMX512/RDM/sACN/Artnet/CRMX control
- NFC+Bluetooth+App integration enables seamless one-touch connection between palm-devices and fixtures for fixture setup, software upgrade, real-time error monitoring, and remote maintenance support

Color System





























Rotating Gobo 2













Framing Shutter

Animation wheel





Beam Angle 3.8°

5				
			A	
	A	A		
	V	H		
1	!		U	1
Distance 5 (m)	10	15	20	25
Llluminance360(90000	40000	22500	14400

Beam Angle 54°

	0			
Distance 5 (m)	10	15	20	25
Llluminance4075 (Lux)	1019	453	255	163

PHOTOMETRICS	
Light Source	1500W LED engine
Output	60000Lm(±5%)
Color Temperature	6000K~6200K
CRI	≥70
LED Life	30000H

3.8~54°

Beam Angle

KEY FEATURES	S
PAN	540°
TILT	270°
Color System	CMY+CTO+Color wheel(6+open)
Gobo System	2 Rotating gobo wheel(6+open)
Animation	Animation wheel with variable speed
Framing system	single blade ±35°、 complete rotatable ±90°
Iris	16 leaves,15%- 100% motorized linear iris
Frost	1°+5° 0% - 100% linear frost
Strobe	1~30Hz
Dimming	Linear/Square/In-verse square/S-curve+4dimming mode(22bit)
Prism	Indexable 4 facet prism+linear prism with variable speed

CONTROL	
Protocol	DMX512/RDM/sACN/Artnet/CRMX/Bluetooth/APP/NFC
Built in programs	YES
Display	40RGB*320, 2.8 inch
Data Connection	IP 3pin (or 5pin) XLR In/Out XLR in/out for DMX, linking up to 32pc

POWER	
Mains	100 - 240 VAC, 50/60Hz
Power connection	TrueCon In
Consumption	1900W /230V
Power Factor	0.98/230V
Ambient	-10°C~45°C

PHYSICAL	
Dimension	517*365*846mm
Weight	51Kg
IP Rating	IP66
Cooling	Heat pipe cooling system with low noise fan
Accessory	Power cable, Omega bracket

